


MITSUBISHI MARINE ENGINE

S6B3-T2MPTAW

335–375 kW | Marine Generator

IMO-T2 and IMO-T3 (SCR option)*

Reliable mechanical engine


ENGINE DATA			
Engine model	S6B3-T2MPTAW	Method of operation	6-cylinder, 4-stroke, water-cooled diesel engine, with direct-injection, turbocharger and air-cooler
Cylinder configuration	6 in-line		
Bore × stroke (mm)	135 x 170		
Total displacement (l)	14.6		
Compression ratio	14.2:1	Cooling method	separate high and low temperature cooling circuit; charge air cooler by closed freshwater system controlled by thermostat (intercooler)
Flywheel and housing	SAE 14 / SAE 10		
Dry weight (kg)	1310		
Aspiration	Turbocharged and after-cooled		

RATING ^{1,2}			
Application	Generator		
Duty Class	Prime		Prime
Output (kW)	335		375
Output (bhp)	449		503
Engine speed (rpm)	1500		1800
Emissions	IMO-T2 and IMO-T3 (SCR option)*		

¹ For rating definitions, please see our website.

² Atmospheric condition: barometric pressure: 100 kPa, ambient temperature: 298 K, relative humidity: 30%.

* The SCR after treatment can be provided through our partners. Please contact MTEE for more information.

STANDARD EQUIPMENT

GOVERNOR (MANDATORY)

- Electronic governor, with speed control box

FUEL SYSTEM

- Flexible fuel supply - and return hoses
- Fuel feed pump
- Fuel fine filters, change-over type
- Fuel injection pump
- Dual walled high-pressure fuel lines
- Fuel injectors

LUBRICATING OIL SYSTEM

- Wet type oil pan with inspection covers
- Oil pressure pump, gear driven
- Lubricating oil filters, change-over type
- By-pass filter
- Oil cooler with thermostat

STARTING AND ELECTRICAL SYSTEM

- Electric starter (Earth floated 24V)
- Alternator, 30 Amps.
- Stop solenoid (ETS)

COOLING SYSTEM

- Fresh water pump including piping and thermostat (HT)
- Front pulley PTO standard

AIR INLET SYSTEM

- Mitsubishi turbocharger
- Air inlet silencer with pre-cleaner
- Inlet air aftercooler or intercooler
- Inlet manifolds or ducts

OTHER


- Mounting brackets for rigid mounting
- Flywheel and housing, SAE standard
- Torsional vibration damper

OPTIONAL EQUIPMENT

SCR Aftertreatment

For more details, please see page 3

DIMENSIONS



More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu

OPTIONAL EQUIPMENT

CERTIFICATION / CLASSIFICATION

- Available in cooperation with major classification societies.

LUBRICATING OIL SYSTEM

- Lubricating oil drain pump
- Pre-lubrication oil system

MONITORING SYSTEM

- Complete digital monitoring system
- Sensor package; sensors mounted on engine with terminal box

STARTING AND ELECTRICAL SYSTEM

- Air starter motor (30 bar)

COOLING SYSTEM

- Cooling system with fresh water pump, V-belt including piping and thermostat (LT)

EXHAUST SYSTEM


- Flexible expansion joint

SCR AFTER TREATMENT SYSTEM

- SCR reactor
- Injection unit
- Dosing unit
- Shoot blower system
- Control system

- Urea pump unit

DIMENSIONS



Dimensions

Engine L x W x H (mm)	1465 x 873 x 1300
SCR unit (On request) size (excl. insulation) L x W x H (mm)	On request
Mixing pipe requirements diameter (DN)*	On request
Mixing pipe length (mm)*	On request

* Insulation of the SCR system is not included in the scope of supply, to be supplied and installed by the shipyard.

More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu