


MITSUBISHI MARINE ENGINE

S12A2-MPTAW

Generator engine · 709–828 kW

IMO-T2, IMO-T3 (SCR option)* and EU-5

Reliable mechanical engine


ENGINE DATA			
Engine model	S12A2-MPTAW	Method of operation	12-cylinder, 4-stroke, water-cooled diesel engine, with direct-injection, turbocharger and air-cooler
Cylinder configuration	12/60°V		
Bore × stroke (mm)	150 x 160		
Flywheel and housing	SAE 18 / SAE 00		
Compression ratio	15.3:1	Cooling method	separate high and low temperature cooling circuit; charge air cooler by closed freshwater system controlled by thermostat (intercooler)
Total displacement (l)	33.93		
Dry weight (kg)	3,380		
Aspiration	Turbocharged and after-cooled		

RATING ^{1,2}		
Application		Generator
Rating	Prime / DEP	Prime / DEP
Output (kW)	709	828
Output (bhp)	950.27	1,109.77
Engine speed (rpm)	1,500	1,800
Gross torque (Nm)	4514	4393
Fuel cons. 100% load (g/kWh)	206	208
Fuel cons. 75% load (g/kWh)	208	205
Fuel cons. 50% load (g/kWh)	212	210
Emissions	IMO-T2, IMO-T3 (SCR option)* and EU-5	
* SCR after-treatment option, see page 3.		

¹ For rating definitions, please see our website.

² Atmospheric condition: barometric pressure: 100 kPa, ambient temperature: 298 K, relative humidity: 30%.

STANDARD AND OPTIONAL EQUIPMENT

AIR INLET SYSTEM

- Air inlet silencer with pre-cleaner
- Inlet air aftercooler or intercooler
- Inlet manifolds or ducts
- Mitsubishi turbocharger

LUBRICATING OIL SYSTEM

- (Optional) Drip tray oil filters
- (Optional) Lubricating oil drain pump
- (Optional) Pre-lubrication oil system
- By-pass filter
- Lubricating oil filters, change-over type
- Oil cooler with thermostat
- Oil pressure pump, gear driven
- Wet type oil pan with inspection covers

OTHER

- Flywheel and housing, SAE standard
- Mounting brackets for rigid mounting
- Torsional vibration damper

FUEL SYSTEM

- (Optional) Drip tray fuel filters
- Dual walled high-pressure fuel lines
- Flexible fuel supply - and return hoses
- Fuel feed pump
- Fuel fine filters, change-over type
- Fuel injection pump
- Fuel injectors

STARTING AND ELECTRICAL SYSTEM

- (Optional) Air starter motor (30 bar)
- Alternator, 30 Amps.
- Electric starter (Earth floated 24V)
- Stop solenoid (ETS)

CLASSIFICATION

- (Optional) We are cooperating with many of the major classification societies.

GOVERNOR (MANDATORY)

- (Optional) Electronic governor, with speed control box
- (Optional) Hydraulic governor

COOLING SYSTEM

- (Optional) Cooling system with fresh water pump, V-belt including piping and thermostat (LT)
- (Optional) Cooling water heater with circulation pump
- Fresh water pump including piping and thermostat (HT)
- Front pulley PTO standard

EXHAUST SYSTEM

- (Optional) Flexible expansion joint
- Stainless steel insulation (SOLAS)



MONITORING SYSTEM

- (Optional) Complete digital monitoring system
- (Optional) Sensor package; sensors mounted on engine with terminal box

OPTIONAL EQUIPMENT

IMO Tier III compliance — SCR after-treatment system available, see page 3.

DIMENSIONS



More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu

OPTIONAL EQUIPMENT

Optional: IMO TIII equipment


SCR AFTER-TREATMENT SYSTEM

- Control system
- Dosing unit
- Injection unit
- SCR reactor
- Shoot blower system

SCR AFTER-TREATMENT SYSTEM

- Urea pump unit

DIMENSIONS



Dimensions

Engine L x W x H (mm)	1948 x 1654 x 1596
SCR unit (SCR25) size (excl. insulation) L x W x H (mm)	893 x 882 x 2349
Mixing pipe requirements diameter (DN)*	400
Mixing pipe length (mm)*	2500

* Insulation of the SCR system is not included in the scope of supply, to be supplied and installed by the shipyard.

More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu