


MITSUBISHI MARINE ENGINE

S6B3-T2MPTAW

320–350 kW | Marine Propulsion

IMO-T2 and IMO-T3 (SCR option)*

Reliable mechanical engine


ENGINE DATA			
Engine model	S6B3-T2MPTAW	Method of operation	6-cylinder, 4-stroke, water-cooled diesel engine, with direct-injection, turbocharger and air-cooler
Cylinder configuration	6 in-line		
Bore × stroke (mm)	135 x 170		
Total displacement (l)	14.6		
Compression ratio	14.2:1	Cooling method	separate high and low temperature cooling circuit; charge air cooler by closed freshwater system controlled by thermostat (intercooler)
Flywheel and housing	SAE 14 / SAE 10		
Dry weight (kg)	1310		
Aspiration	Turbocharged and after-cooled		

RATING ^{1,2}			
Duty Class	UCD		HD
Output (kW)	320		350
Output (bhp)	429		469
Engine speed (rpm)	1940		2000
Average fuel consumption (l/h)³	62.4		—
Running Hours	7000 - unlimited		5000-7000
Propulsion System	CPP/FPP		CPP/FPP
Emissions	IMO-T2 and IMO-T3 (SCR option)*		

¹ For rating definitions, please see our website.

² Atmospheric condition: barometric pressure: 100 kPa, ambient temperature: 298 K, relative humidity: 30%.

³ Fuel consumption is based on ISO3046/1 with +5% tolerance at rated power, weighing 836 g/liter and a LHV of 42,780 kJ/kg, excluding pump. Average fuel consumption recommended by ISO8178 (E3 standard test cycle for propulsion application FPP).

* The SCR after treatment can be provided through our partners. Please contact MTEE for more information.

STANDARD EQUIPMENT

GOVERNOR (MANDATORY)

- Hydraulic governor

FUEL SYSTEM

- Flexible fuel supply - and return hoses
- Fuel feed pump
- Fuel fine filters, change-over type
- Fuel injection pump
- Dual walled high-pressure fuel lines
- Fuel injectors

LUBRICATING OIL SYSTEM

- Wet type oil pan with inspection covers
- Oil pressure pump, gear driven
- Lubricating oil filters, change-over type
- By-pass filter
- Oil cooler with thermostat

STARTING AND ELECTRICAL SYSTEM

- Electric starter (Earth floated 24V)
- Alternator, 30 Amps.
- Stop solenoid (ETS)

COOLING SYSTEM

- Fresh water pump including piping and thermostat (HT)
- Front pulley PTO standard

AIR INLET SYSTEM

- Mitsubishi turbocharger
- Air inlet silencer with pre-cleaner
- Inlet air aftercooler or intercooler
- Inlet manifolds or ducts

OTHER


- Mounting brackets for rigid mounting
- Flywheel and housing, SAE standard
- Torsional vibration damper

OPTIONAL EQUIPMENT

SCR Aftertreatment

For more details, please see page 3

DIMENSIONS



More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu

OPTIONAL EQUIPMENT

CERTIFICATION / CLASSIFICATION

- Available in cooperation with major classification societies.

EXHAUST SYSTEM


- Stainless steel insulation (SOLAS)
- Flexible expansion joint

SCR AFTER TREATMENT SYSTEM

- SCR reactor
- Injection unit
- Dosing unit
- Shoot blower system
- Control system

- Urea pump unit

DIMENSIONS



Dimensions

Engine L x W x H (mm)	1465 x 873 x 1300
SCR unit (On request) size (excl. insulation) L x W x H (mm)	On request
Mixing pipe requirements diameter (DN)*	On request
Mixing pipe length (mm)*	On request

* Insulation of the SCR system is not included in the scope of supply, to be supplied and installed by the shipyard.

More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu